



Desktop Touch Monitor



Product Features

- . Stable base made for touch
- . Choice of touch technologies
- . Desk or Wall mount
- . Agency approvals CE, FCC, ROHS CB certified.

Specification		IR Model	RE Model	SAW Model	PCAP Model
Series		DT Waterproof	DT Dust Proof		
LCD Type		Active Matrix TFT-LCD with LED Backlight			
Display Active Area		338 mm x 272 mm			
Supported Colours		16.7 Million			
Contrast Ratio					
Native Resolution		1280 x 1024			
Aspect Ratio		5:4			
Display Response Time (typ)		5 ms			
Brightness(Typ)	Pure LCD Panel	250 cd/m ²	250 cd/m ²	250 cd/m ²	250 cd/m ²
	With PCAP Touchscreen	225 cd/m ²	200 cd/m ²	225 cd/m ²	212 cd/m ²
Brightness from 300-1000cd/m ² can be customised					
Viewing Angle (Typ at CR>10)	Horizontal (Left/Right)	85° / 85°			
	Vertical (Up/Down)	80° / 80°			
Video Input		VGA			
Frequency		30-80 KHz /60-75 Hz			
Power Supply		Type: Power Brick Input Voltage: 100-240 VAC 50-60 Hz			
Environment	Operating Temp	0-50°C			
	Storage Temp	-20-60°C			
	Operating RH	20%-80%			
	Storage RH	10%-90%			
MTBF		50.000 hours			
Backlight Life (Typ)		50.000 hours			
Weight (NW/GW)		N.W: 5.05 Kg G.W 6.35 Kg			
Power Consumption		15.3 W Max			
Standby Power consumption		0.56 W			
Mount Interface		1) VESA 75 mm and 100 mm 2) Mount bracket, horizontal or vertical (standard mount brackets supplied)			
Touch System Interface		USB			
Touch Response Time		10Ms			
Agency Approval		CE, FCC, ETL, CB, RoHS ,CCC			
Warranty		3 years			